

COMPTROL BEARING BLOCKS FOR 1.130 DIAMETER BALLSCREWS



Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-203-A	Driven	66-203-B	Driven	66-203-C	Driven
	66-203-A1	Non-Driven	66-203-B1	Non-Driven	66-203-C1	Non-Driven

See drive end shaft extension detail below.

Note: For each Type A or A1 bearing block required, add .188" to ballscrew thread length.

Cut-Off Flange Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-303-A	Driven	66-303-B	Driven	66-303-C	Driven
	66-303-A1	Non-Driven	66-303-B1	Non-Driven	66-303-C1	Non-Driven

See drive end shaft extension detail below.

Note: For each Type A or A1 bearing block required, add .188" to ballscrew thread length.

Base Mount	Model	Shaft End	Model	Shaft End	Model	Shaft End
	66-403-A	Driven	66-403-B	Driven	66-403-C	Driven
	66-403-A1	Non-Driven	66-403-B1	Non-Driven	66-403-C1	Non-Driven

See drive end shaft extension detail below.

.297 diameter thru used at assembly

Note: For each Type A or A1 bearing block required, add .188" to ballscrew thread length.

Standard Drive Extension	Mounting Hole Detail	Model Number Designation
		<p>66 - X 0 3 - X X</p> <ul style="list-style-type: none"> Bearing Block Mounting Style <ul style="list-style-type: none"> 2 = Flange 3 = Cut-Off Flange 4 = Base 1.130 Diameter Ballscrew Shaft End <ul style="list-style-type: none"> Blank = Driven 1 = Non-Driven Bearing Type <ul style="list-style-type: none"> A = Radial B = Duplex C = Spaced

Notes

- All dimensions in inches unless otherwise specified.
- Refer to Page 3 for Nominal Load Capacities.
- End journals must be machined per dimensions on Page 13.
- Custom and metric bearing block assemblies and/or drive end journals are available.
- Dimensions and specifications subject to change without notice.